

PRODUCT
SPECIFICATION



PHOENIX 3300

TROMMEL SCREEN



PHOENIX 3300

The Phoenix 3300 is designed to offer unrivalled production throughput and application flexibility.

Terex Ecotec's Phoenix 3300 trommel screen is designed to offer unrivalled production throughput and application flexibility. The robust design with optional features such as heavy duty tipping grid or double deck vibrating grid make the Phoenix 3300 the most versatile trommel on the market today. The machine performs equally well in heavy C&D applications as it does in high volume compost production. The 180° swivel fines conveyor, with a 5.8m (19') discharge, means the machine can generate massive stockpiles. This swivel feature can be controlled via a radio remote while the machine is in operation, minimising downtime.

A powerful four wheel drive system with high performance friction grip wheels is used to turn the

trommel drum giving operators the ability to run bi-directionally. Woven mesh or heavy duty punch plate panels can be fitted to the trommel drum ensuring all application requirements are met.

Caterpillar Tier 3 or Tier 4 engines combined with powerful hydraulics and auto feeder speed control guarantee the machine is always working at its optimum. A fifth wheel connection, triple axle bogie and a rapid setup time make the machine highly mobile.

The Phoenix 3300 is highly efficient in the separation and processing of wood chippings, top soil, compost, green waste, C&D waste and aggregates.



TECHNICAL DATA

TRANSPORT DIMENSIONS	POWERPACK & CONTROL	BOGIE
Width: 3.0m (9' 10")	Caterpillar C71 Tier 3, 151kW (202 hp), 2200rpm max	3 axles, 8 studs
Height: 4.1m (13' 6")	Caterpillar C4.4 Tier 4i 129kW (173hp), 2200rpm max (option)	Suspension type leaf spring
Length: 21.1m (69' 2")	Caterpillar C4.4 Tier 4f 129kW (173hp), 2200rpm max (option)	Super single c/w 385/65 R22.5 tyres
Weight: 37,500kg (82,673lbs)	Fuel tank capacity 610L (134 Gal) (161 US Gal)	Fifth wheel connection
	Hydraulic tank 714L (157 Gal) (189 US Gal)	Airbrakes
	Excellent service access	
	Powerful hydraulics	
WORKING DIMENSIONS	COLLECTION CONVEYOR	OPTIONS
Width: 15.8m (51' 8")	1500mm (59") 3 ply plain belt, 4 + 2 covers	Remote control tipping grid 100mm (4")
Length: 32.3m (105' 9")	Fully skirted & sealed	Remote control tipping grid 150mm (6")
Height: 5.9m (19' 4")	Variable speed control	2 Deck vibrating grid c/w tri-axle bogie
		Tipping grid discharge chute
		Heavy duty woven mesh
		Punch plate
		Different colour paint
HOPPER AND BELT FEEDER	FINES DISCHARGE CONVEYOR	
7.8m ³ (10.2yd ³) capacity	1200mm (47") 3 ply plain belt, 4 + 2 covers	
4.6m (15' 1") feeder length	Remote control 180° swivel	
1500mm (59") 3 ply plain belt, 4 + 2 covers	Variable operating angle 10° - 28°	
Variable speed control c/w load sensing and automatic feeder shutdown	Discharge height 5.8m (19') @ 28°	
Hopper extensions	Variable speed control	
	Hydraulic folding	
DRUM	OVERSIZE CONVEYOR	
9.31m (30' 6") Length	1200mm (47") 3 ply chevron belt, 4 + 2 covers	
2.32m (7' 6") Diameter	Full length skirting	
Friction four wheel drum drive system	Variable speed control	
Variable speed control	Hydraulic folding	
Mesh or Punch plate panels	Variable operating angle 10° - 28°	
Inclined drum	Discharge height 4.16m (13' 7") @ 28°	
Variable operating angle 4.5° - 6°		
Tumbling action c/w nylon cleaning brushes		
Service access doors for maintenance		

Specification subject to change without notice



DUNGANNON

32 Farlough Road
Dungannon, Co. Tyrone
BT71 4DT, Northern Ireland

Tel: +44 (0) 28 87 718 500

NEWTON

22 Whittier Street
Newton, New Hampshire
USA, 03858

Tel: +1 (603) 382 0556

Dealer Stamp:

December 2017. The material in this document is for information only and is subject to change without notice. Terex Ecotec assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Any product performance figures given in this brochure are for guidance purposes only. This information does not constitute an expressed or implied warranty or guarantee, but shows text examples provided. These results will vary depending on product settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only. Some or all of the machines in the illustrations may be fitted with optional extra. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries © 2017 Terex Corporation.