MONTABERT®

DRILLING ATTACHMENT

CPA 30-095



HOLE DIAMETER	MAX DEPTH	CARRIER WEIGHT
64-102 mm 2.5-4"	29 m 95'	28-35 t 61,729-77,162 lb

TRANSFORMS AN EXCAVATOR INTO A SURFACE DRILL RIG

EQUIPPED WITH MONTABERT HC95 HYDRAULIC DRIFTER

COMPATIBLE WITH QUICK COUPLERS

WATER MIST AND GROUTING HEAD COMPATIBLE

UTILITY WORKS, QUARRY OPERATIONS, TRENCHING, PRE-SPLITTING, GROUND SUPPORT

BENEFITS

- **Intelligent rock sensing technology:** reduce production cost with drilling tool protection and optimize blasting with precision drilling.
- **Standard radio remote control:** operate the drill without excavator control system modification and adjust drilling parameters from the radio control.
- **Operation:** optimize your drilling cycle with an automatic rod adding system. Improve drilling quality with a 2D/3D angle indicator.
- **Versatility:** utility work, construction site, drill & blast, high reach and rough terrain access with the agility of an excavator.
- **Hydraulic dust collector:** control the dust in the environment with a high efficiency vaccum system.
- **Remote product support:** Bluetooth connection with smartphone for diagnostics, monitoring and factory assistance.

CPA
30-095

DRILLING ATTACHMENT

LICENSE TO DRILL

WEIGHT (WITH RODS AND DUST COLLECTOR, WITHOUT ADAPTER PLATE)		
T38 (LB/KG)	6,328	2,870
T45 (LB/KG)	6,526	2,960
T51 (LB/KG)	6,702	3,040



DRIFTER HC95		
POWER (HP / KW)	24	18
STRIKE FREQUNECY (MIN-MAX, HZ / BPM)	48 - 57	2,900 - 3,400
TORQUE (MAX, FT. LB / NM)	704	955

OPERATING INFOMRATION		
CARRIER WEIGHT* (MIN-MAX, LB/T)	61,729 - 77,162	28 - 35
OIL FLOW (GPM / L/MIN)	52.8	200
WORKING PRESSURE (PSI/BAR)	3,191	220
FLUSHING AIR FLOW (VARIES ACCORDING TO DRILL BIT DIAMETER, CFM/ L/MIN)	247	7,000
ELECTRICAL SUPPLY (V DC)		24

*Always check the manufacturer's lift capacity chart to ensure the hydraulic attachment is suitable for your excavator. Exceeding limits may cause damage or safety risks.

FEATURES HC95
AIR OR WATER FLUSHING
FULL HYDRAULIC REVERSE PERCUSSION
DAMPING SYSTEM FOR ENHANCED SHANK LIFE

MAST CAPACITY		
FIRST ROD LENGTH (FT/MM)	16	4,876
EXTENSION RODS LENGTH (FT/MM)	12	3,657
SINGLE PASS HOLE LENGTH (IN/MM)	13.8	4,200
FEED ANCHORING STROKE (ROCK APPROACH, FT/MM)	3.4	1,050
TELESCOPIC DUST HOOD STROKE (FT/MM)	0.5	160
TILT	+/- 47° (x4 mounting positions)	

	T38 / R38 / T51	
ROD CHANGER CAPACITY	7 rods	
MAXIMUM HOLE LENGTH (FT/ MM)	98	29,860

DRILLING FEATURES
2D / 3D ANGLE & ORIENTATION INDICATOR
TARGET DEPTH AUTOSTOP
DEPTH MEASUREMENT
ON SCREEN PRESSURE DISPLAY
AUTOMATIC RETURN
AUTOMATIC RATTLING FOR ROD EXTRACTION
TOOL LIFE MONITORING
DRILLED HOLES LOG
AUTOMATIC ROD ADDING
DRILLING MODES (COLLARING, MANUAL, AUTOMATIC)
PERCUSSION POWER REGULATION
ANTI-JAMMING
OPERATOR PROXIMITY DETECTION (OPTION)

The content of this brochure constitutes non-binding information and may be changed at any time without notice. Montabert gives, and the brochure contains, no warranties whatsoever, express or implied. All the contents, including but not limited to text, images, graphics are all subject to copyright and all intellectual property protection. Their use or misuse is strictly prohibited. Montabert brand and logo used herein are the property of Montabert. Nothing contained on this document shall be construed as constituting any commitment by Montabert or as granting any license or right to use any intellectual property. ©2026 Montabert. All rights reserved.

CE UKCA

montabert.com

EN-CPA30-095-V012026